23j
Wa

WAYNE
GYMNASIUM SEATING

MODEL 50—VERTICAL FRONT
WALL OR FLOOR ATTACHED • MANUAL OPERATION





WAYNE
GYMNASIUM SEATING

MODEL 50-R—RECESSED
WALL ATTACHED • MANUAL OPERATION





WAYNE
GYMNASIUM SEATING

MODEL 50-M—MOVABLE
SELF-SUPPORTING • MANUAL OPERATION WITH TRUCKS





WAYNE
GYMNASIUM SEATING

MODEL 50-S, 50-X—HIGH VISIBILITY
FOR TWO LEVEL SEATING • MANUAL OPERATION

WAYNE
GYMNASIUM SEATING

MODEL 70—CONTINUOUS SEATING
AUTOMATIC POWER OPERATION





WAYNE
GYMNASIUM SEATING

MODEL 30—FOLDING BLEACHERS
WALL ATTACHED • MANUAL OPERATION





WAYNE
GYMNASIUM SEATING

MODELS 50-RR—50-RRFM—50-RRFO—REVERSE ROLL





WAYNE MODEL 50 VERTICAL FRONT

engineering excellence • design efficiency • greater seating value



GIRDER BRIDGE DESIGN—Two column construction permits front and back riser boards, functioning as parallel girders, to transmit the spectator load directly through the strong steel columns to the floor. This design is comparable to the joists of a floor or the functions of the girders in a bridge.

2 MOVING PARTS PER ROW—Wayne's original alignment frame design reduces friction, insures straight, smooth opening and closing. Eliminates binds during operation, even with off-center pushing or pulling.



RISER BOARD UP—Brakes off the floor—ready to roll



GYMSTAND OCCUPIED—spectator load is on the floor



RISER BOARD DOWN—8 brakes per unit firmly contact the floor



GYMSTAND UNOCCUPIED—load is on the wheels

NON-GROOVE ROLLING SYSTEM—Wayne's wheel assembly, housed in the Rolling Foot, carries the columns of each row separately side by side, not in the same plane. This efficient design distributes the load; eliminates floor grooving; makes the stand easy to open and close.

SELF-LOCKING BRAKES—The hinged front row riser board operates Wayne's efficient self-locking system. When the front riser board is lowered, the locking system automatically makes contact with the gym floor at 8 points. Units cannot shift, slide or lose position. When the front riser is lifted, the 8 brakes automatically lift from the floor.

LOAD DISTRIBUTION—When the stand is occupied, the live load is carried directly to the floor through the strong steel columns. Wayne's Rolling Foot, a unique system that provides 65 square inches of floor contact area per row, exceeds by more than 100% any competitive design, distributes the load over a broad area, insures stability.

SWAY BRACES—Two or more diagonal sway braces per row add stability to Wayne Rolling Gymstands. These strong steel angles transmit any sway action to the floor through the column foot

USE ANY NUMBER OF ROWS—Wayne's positive self-row-locking system permits any number of rows to be used. Simply by rolling out the number of rows required and locking the front riser board, the entire assembly locks in position ready for use for social affairs, dances, etc.

STANDARD DIMENSIONS

10¼" RISE-PER-ROW

22" DEPTH-PER-ROW

DETAIL • DIMENSIONS



ROLLING GYMSTAND MODELS 50, 50-R, 50-S, 50-X, 50-RR, 50-RRFM, 50-RRFO, 70

No. of Rows	22" Depth Open *	22" Depth Closed *	24" Depth Open *	24" Depth Closed *	Height 10¼" Rise Per Row**	Min. Unit Length	No. Seats 16'0" Unit
	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	
3	4-6	2-8	4-10	2-10	3- 1½	4-6	36
4	6-4	2-8	6-10	2-10	3-11¾	5-10	48
5	8-2	2-8	8-10	2-10	4-10	6-5	60
6	10-0	2-8	10-10	2-10	5- 8¼	6-9	72
7	11-10	2-8	12-10	2-10	6- 6½	7-2	84
8	13-8	2-8	14-10	2-10	7- 4¾	7-6	96
9	15-6	2-8	16-10	2-10	8-3	7-11	108
10	17-4	2-8	18-10	2-10	9-1¼	8-3	120
11	19-2	2-8	20-10	2-10	9-11½	8-8	132
12	21-0	2-8	22-10	2-10	10-9¾	9-0	144
13	22-10	2-8	24-10	2-10	11-8	9-5	156
14	24-8	2-8	26-10	2-10	12-6¼	9-9	168
15	26-7	2-9	28-10	2-10	13-4½	13-10	180
16	28-5	2-9	30-10	2-10	14-2¾	13-10	192
17	30-3	4-7	32-10	4-10	15-1	13-10	204
18	32-1	4-7	34-10	4-10	15-11¼	13-10	216
19	33-11	4-7	36-10	4-10	16-9½	13-10	228
20	35-9	4-7	38-10	4-10	17-7¾	13-10	240
21	37-7	4-7	40-10	4-10	18-6	13-10	252
22	39-5	4-7	42-10	4-10	19-4¼	14-3	264
23	41-3	4-7	44-10	4-10	20-2½	14-3	276

HEIGHT OF SEAT ABOVE FOOTREST IS 17 INCHES

* For comfort, top seat should be set about 3" from wall on all models except model 70 where distance should be 5". 12" top seatboard is provided on model #70 to assure standard 3" offset. Therefore ADD 3" to the dimensions from 3 to 14 rows and add 2" to the dimensions from 15 to 23 rows. Allow 1" to 2" clearance between units and 1½" to 2" clearance between end units and walls or other obstructions.

** (Model 50-S) For 11⅜" rise-per-row, add to height 1⅛" for each row except the front row.

** (Model 50-X) For 13⅜" rise-per-row, add to height 3⅛" for each row except the front row.

MOVABLE ROLLING GYMSTAND MODEL 50-M
Maximum 14 Rows

No. of Rows	22" Depth Open	22" Depth Closed	22" Depth Closed on Trucks	24" Depth Open	24" Depth Closed	24" Depth Closed on Trucks	Height 10¼" Rise Per Row	Minimum Length Movable	No. Seats 16'0" Unit
	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	Ft.-In.	
3	5-3½	3-5½	4-1⅜	5-7½	3-7½	4-3⅜	3-1½	6-3	36
4	7-1½	3-5½	4-1⅜	7-7½	3-7½	4-3⅜	3-11¾	7-7	48
5	8-11½	3-5½	4-1⅜	9-7½	3-7½	4-3⅜	4-10	8-2	60
6	10-9½	3-5½	4-1⅜	11-7½	3-7½	4-3⅜	5-8¼	8-6	72
7	12-7½	3-5½	4-1⅜	13-7½	3-7½	4-3⅜	6-6½	8-11	84
8	14-5½	3-5½	4-1⅜	15-7½	3-7½	4-3⅜	7-4¾	9-3	96
9	16-3½	3-5½	4-1⅜	17-7½	3-7½	4-3⅜	8-3	9-8	108
10	18-1½	3-5½	4-1⅜	19-7½	3-7½	4-3⅜	9-1¼	10-0	120
11	19-11½	3-5½	4-1⅜	21-7½	3-7½	4-3⅜	9-11½	10-5	132
12	21-9½	3-5½	4-1⅜	23-7½	3-7½	4-3⅜	10-9¾	10-9	144
13	23-7½	3-5½	4-1⅜	25-7½	3-7½	4-3⅜	11-8	11-2	156
14	25-5½	3-5½	4-1⅜	27-7½	3-7½	4-3⅜	12-6¼	11-6	168

HEIGHT OF SEAT ABOVE FOOTREST IS 17 INCHES

For 11⅜" rise-per-row, add to height 1⅛" for each row except the front row.

For 13⅜" rise-per-row, add to height 3⅛" for each row except the front row.



WAYNE MODEL 70

continous seating • automatic power operation

EFFICIENT, NOISELESS MOTORIZED DRIVE SYSTEM*

1. Gearhead Reduction Motor
2. Chain Drive and Adjustable Torque-Limiting Safety Coupling
3. Jack Shaft
4. Sprocket and Chain Drive
5. Drive Reels
6. Rigid Pusher Linkage
7. Wayne-Weld Continuous Boards*

Wayne Motorized Rolling Gymstands are opened or closed by a steady force applied to the front row as the hinged links of steel channel wind or unwind and roll smoothly and noiselessly along the floor.

- No floor track required
- No building extras needed
- Operates on 208 or 220 volt power source
- Straight line operation—no binding, wandering or jamming
- Can be stopped and locked in any position during operation

9-row continuous Model 70 in open position

9-row continuous Model 70 in closed position

*Patent Pending

THE WAYNE MODEL 30 FOLDING BLEACHER

EASY ROLLING	ENAMELED TUBULAR STEEL UNDER-STRUCTURE	ATTRACTIVE LACQUERED DOUGLAS FIR WOOD	NON-MARKING, RUBBER FACED, PLASTIC WHEELS	OPENS AND CLOSES IN ONE CONTINUOUS MOTION	CAN BE LOCKED IN ANY POSITION



SLOPING FRONT
WHEN CLOSED

SEATING EFFICIENCY AT LOW COST!—Mounted on 4″ diameter wheels under all columns except the stationary rear columns, the Wayne Model 30 Folding Bleacher rolls back against the wall in one continuous operation to form a sloping front.

GENERAL SPECIFICATIONS

1. DESIGN AND CONSTRUCTION

The seating shall be designed and constructed to support, in addition to its own weight, a live load of 120 pounds per linear foot of seatboard, plus 120 pounds per linear foot of footboard, and to resist by adequate diagonal bracing a horizontal sway load applied lengthwise to the seats, of 24 pounds per linear foot of seatboard. Under these loads, stresses in steel shall conform to the Standard Specification of the American Institute of Steel Construction, and stresses in wood shall not exceed those recommended by U. S. Forest Products Laboratory.

2. FINISH

All steel parts of the understructure shall be properly cleaned and finished in gray enamel.

All wood parts shall be sanded and finished with natural hot sprayed lacquer.

3. GUARANTEE

The manufacturer shall guarantee that all work done under these specifications is free from defects in materials and workmanship for a period of one year from date of completion of installation.

INDIVIDUAL MODEL SPECIFICATIONS

Model 30 Folding Bleacher

4. STANDARD DIMENSIONS

Depth per row—22 inches
Rise per row—8½ inches
Seat height—17½ inches

5. UNIT CONSTRUCTION

Each unit shall be complete in itself, consisting of tubular steel understructure, footboards, seatboards and riser boards, connected to form one integral assembly. Each column of the unit (except the stationary rear columns) shall be equipped with a 4 inch diameter wheel, with oil-less bearings, made of a rubber faced plastic composition which will not mark or dent the floor.

When fully closed, the front of the unit shall form a sloping surface.

6. SEATBOARDS, FOOTBOARDS AND RISER BOARDS

All boards shall be Douglas Fir of quality as defined by "Standard Grading and Dressing Rules No. 15" as published by the West Coast Lumbermen's Association. The edges and ends of all boards shall be eased.

Seatboards—clear solid lumber as defined by Rule 151-b., 5/4″ x 10″ before surfacing.

Footboards—solid lumber as defined by Rule 123-a., 2″ x 10″ before surfacing.

Riser boards—clear solid lumber as defined by Rule 151-b., 1″ x 8″ before surfacing.

7. INSTALLATION

Installation shall be done by the manufacturer's regularly authorized representative. Units shall be fastened to the wall with proper attachments. All units shall be adjusted to operate easily.

Model 50 Vertical Front Rolling Gymstand

4. STANDARD DIMENSIONS

Depth per row—22 inches
Rise per row—10¼ inches
Seat height—17 inches

5. UNIT CONSTRUCTION

Each unit shall be complete in itself, consisting of steel understructure, footboards, seatboards and vertical riser boards, connected to form one integral assembly. Each column of the unit (except the stationary rear columns) shall be equipped with two 3 inch diameter wheels, with oil-less bearings, made of a rubber faced plastic composition which will not mark or dent the floor. When live load is applied, the wheel housing (rolling foot) shall establish contact with the floor, to transmit live load directly to the floor.

Each unit shall be equipped with rotating alignment frames to keep the rows parallel at all times.

Each unit shall be equipped with a cylinder lock to lock it automatically in both the open and closed position. In addition, the front row of each unit shall be equipped with self-setting rubber brakes.

When fully closed, the front of the unit shall form a vertical surface.

6. SEATBOARDS, FOOTBOARDS AND RISER BOARDS

All boards shall be Philippine Mahogany equal to FAS and Selects as established by the National Hardwood Lumber Association or Douglas Fir as defined by Rule 151-b of "Standard Grading and Dressing Rules No. 15" as published by the West Coast Lumbermen's Association. The edges and ends of all boards shall be eased.

Seatboards—5/4″x10″ before surfacing.
Footboards—5/4″x10″ before surfacing.
Riser boards—5/4″ x width to fully close the vertical gap between corresponding foot and seatboards.

7. INSTALLATION

Installation shall be done by the manufacturer's regularly authorized representative. Units shall be fastened in place with proper attachments. All units shall be adjusted to operate easily.

Model 70 Continuous Seating-Automatic Power Operation

4. STANDARD DIMENSIONS

Depth per row—22 inches
Rise per row—10¼ inches
Seat height—17 inches

5. CONSTRUCTION OF SEATING SECTIONS

Each section shall be constructed as a continuous, uninterrupted length of seats and shall consist of steel understructure, footboards, seatboards and vertical riser boards connected to form one integral assembly. The boards shall be installed so that no breaks or gaps occur in the entire length of the section.

Each column of the section (except the stationary rear columns) shall be equipped with two 3 inch diameter wheels. When live load is applied, the wheel housing (rolling foot) shall establish contact with the floor.

6. POWER OPERATION

Each section shall be installed with self-contained, automatic power operation. The opening and closing of the sections shall be controlled by a spring loaded key switch conveniently located. The power system shall be designed so that one or more rows may be used at any time. The movement of the section to the extreme open or closed positions shall be controlled by limit switches. Each section shall be powered by a single motor to assure positive alignment at all times. The power shall be transmitted from the motor to drive reels and rigid pusher bars by means of a steel jack shaft and chain drive linkage.

Each section shall be equipped with a simple and positive means for disengaging the drive mechanism so that the section can be opened manually in case of power failure.

7. SEATBOARDS, FOOTBOARDS AND RISER BOARDS

All boards shall be Philippine Mahogany equal to FAS and Selects as established by the National Hardwood Lumber Association or Douglas Fir as defined by Rule 151-b of "Standard Grading and Dressing Rules No. 15" as published by the West Coast Lumbermen's Association. The edges and ends of all boards shall be eased.

Seatboards—5/4″x10″ before surfacing.
Footboards—5/4″x10″ before surfacing.
Riser boards—5/4″ x width to fully close the gap between corresponding foot and seatboards.

8. INSTALLATION

Installation shall be done by the manufacturer's regularly authorized representative. Sections shall be fastened in place with proper attachments. All sections shall be adjusted to operate easily.

PLEASE NOTE: Wayne Iron Works continually pursues a program of design and product improvement for better spectator seating. When such improvements occur, or, when conditions exist over which we have no control, Wayne Iron Works reserves the right to supply equipment considered to be standard at the time of shipment.

PLANNING • SALES • SERVICE

Wayne equipment is planned, sold and serviced by factory trained representatives located throughout the United States. For immediate information or guidance call the Wayne Representative nearest you or write the factory direct.

ALABAMA
STANDARD SCHOOL SERVICE
3827 First Avenue, N.
Birmingham 6 LY 2-8181

ALASKA
J. K. GILL CO.
Anchorage

ARIZONA
McKINNEY, ROBERT G., CO.
P.O. Box 2483
Phoenix WH 5-5243

ARKANSAS
ARKANSAS SCHOOL SERVICE, INC.
201 Victory Road
P.O. Box 2801
Little Rock FR 6-2417

CALIFORNIA
AUSTIN-BENTLEY SEATING CO.
529 N. La Cienega Blvd.
Los Angeles 48 OL 5-8410

AUSTIN SAFE AND DESK, LTD.
1320 Fifth Avenue
San Diego 1 BE 3-6601

BROOKMAN COMPANY, INC., THE
2833 Third Street
San Francisco 7 AT 8-0644

COLORADO
HORBLIT AND COMPANY
2329 Champa Street
Denver 5 AM 6-2691

CONNECTICUT
FISHER, E. A., CO.
P.O. Box 640
336 Mamaroneck Avenue
Mamaroneck, New York OW 8-3486

DELAWARE
DEGLER WHITING, INC.
132 Lancaster Avenue, W.
Wayne, Pennsylvania MU 8-5518

DISTRICT OF COLUMBIA
STOTT, CHAS. G., AND CO., INC.
1310 New York Avenue, N.W.
Washington 5 NA 8-4181

FLORIDA
WIMER, JOHN M.
P.O. Box 631
Deland RE 4-5235

MYERS, DON F.
365 Harbor Drive
Key Biscayne
Miami 49 EM 1-2696

GEORGIA
McGREGOR CO., THE
321 East Clayton Street
Athens LI 3-5266

IDAHO
GILL, J. K., CO.
408 S.W. Fifth Avenue
Portland 4, Oregon CA 8-8681

LARICK SPECIALTIES, INC.
955 Folsom Avenue
Salt Lake City 4, Utah DA 8-8534

ILLINOIS
CARROLL SEATING COMPANY
5107 W. Division Street
Chicago 51 MA 6-3820

FRANKLIN-LEE COMPANY
12801 South Halsted Street
Chicago 28 IN 8-8600

BLACKWELL-WIELANDY CO., THE
1605 Locust Street
St. Louis 6, Mo CE 1-0630

INDIANA
BURNS SALES COMPANY
P.O. Box 5023
Indianapolis AT 3-2519

IOWA
HOLLEY SCHOOL SUPPLY CO.
100 East Grand Avenue
Des Moines 7 CH 3-6247

TRIANGLE SCHOOL SERVICE
1401 "C" Avenue
Sioux Falls, S. D. 8-7813

KANSAS
BOWLUS SCHOOL SUPPLY CO.
1015 N. Broadway
Pittsburg 888

KENTUCKY
BURRIS, INC.
223 E. 8th Street
Cincinnati, Ohio GA 1-1549

MASSEY SEATING CO.
160 Hermitage Avenue
Nashville, Tennessee AL 5-8459

LOUISIANA
LOUISIANA SCHOOL SUPPLY CO.
Acme Life Insurance Bldg.
833 Howard Avenue
New Orleans 12 MA 0643

MAINE
HAMMETT, J. L., CO.
Kendall Square
Cambridge 42, Mass. TR 6-5230

MARYLAND
STOTT, CHAS. G., AND CO., INC.
1310 New York Avenue, N.W.
Washington 5, D.C. NA 8-4181

MASSACHUSETTS
HAMMETT, J. L., CO.
Kendall Square
Cambridge 42 TR 6-5230

MICHIGAN
UNIVERSITY SCHOOL EQUIPMENT CO.
2300 Washtenaw
Ann Arbor NO 3-4248

MINNESOTA
ST. PAUL BOOK AND STATIONERY CO.
Cor. of Sixth and Cedar Sts.
St. Paul 1 CA 2-8421

MISSISSIPPI
MARTIN SCHOOL EQUIPMENT CO.
303 East Hamilton Street
P.O. Box 259
Jackson FL 4-4671

MISSOURI
BLACKWELL-WIELANDY CO., THE
1605 Locust Street
St. Louis 6 CE 1-0630

BOWLUS SCHOOL SUPPLY CO.
1015 N. Broadway
Pittsburg, Kansas 888

NEBRASKA
UNIVERSITY PUBLISHING COMPANY
1126 "Q" Street
Lincoln 2 2761

NEVADA
LARICK SPECIALTIES, INC.
955 Folsom Avenue
Salt Lake City 4, Utah DA 8-8534

NEW HAMPSHIRE
HAMMETT, J. L., CO.
Kendall Square
Cambridge 42, Mass. TR 6-5230

NEW JERSEY
MORGAN, GEORGE H.
186 Lake Avenue
Fair Haven SH 7-3212

NEW MEXICO
TIANO SPORTING GOODS CO.
228 Galisteo Street
Santa Fe 2-0751

NEW YORK
MODERN FOLD SALES CORP.
2267 Delaware Avenue
Buffalo 16 VI 5103

FISHER, E. A., CO.
P.O. BOX 640
336 Mamaroneck Avenue
Mamaroneck OW 8-3486

AMERICAN MANUFACTURING SALES CO.
6048 Riverdale Avenue
New York City 71 KI 9-7002

CASCADE SCHOOL SUPPLIES
1 Brown Street
North Adams, Mass. MO 3-3716

NORTH CAROLINA
HOLMES, J. NORWOOD
Goldsboro RE 4-5008

NORTH DAKOTA
WOODMANSEE'S INC.
114 — 4th Street
Bismarck CA 3-6250

OHIO
BURRIS, INC.
223 E. 8th Street
Cincinnati GA 1-1549

KYSER SALES COMPANY, W. M.
3425 Youngstown Road, S.E.
P.O. Box 366
Warren EX 4-5631

OKLAHOMA
THOMPSON BOOK AND SUPPLY CO.
926 East Main Street
Ada FE 2-4074

OREGON
GILL, J. K., CO.
408 S.W. Fifth Avenue
Portland 4 CA 8-8681

PENNSYLVANIA
DEGLER-WHITING, INC.
P.O. Box 10604
Pittsburgh 35 CH 2-4477

DEGLER-WHITING, INC.
P.O. Box 102
Sinking Springs OR 8-9711

DEGLER-WHITING, INC.
132 Lancaster Avenue, W.
Wayne MU 8-5518

RHODE ISLAND
HAMMETT, J. L., CO.
Kendall Square
Cambridge 42, Mass. TR 6-5230

SOUTH CAROLINA
HOLMES, J. NORWOOD
Goldsboro, N. C. RE 4-5008

SOUTH DAKOTA
TRIANGLE SCHOOL SERVICE
1401 "C" Avenue
Sioux Falls 8-7813

TENNESSEE
MASSEY SEATING CO.
160 Hermitage Avenue
Nashville AL 5-8459

TEXAS
BICKLEY BROTHERS, INC.
2017 Preston Avenue
Houston 2 CA 2-9577

PILLOW-McMASTERS INC.
1019 E. Missove Street
El Paso KE 2-9332

UTAH
LARICK SPECIALTIES, INC.
955 Folsom Avenue
Salt Lake City 4 DA 8-8534

VERMONT
HAMMETT, J. L., CO.
Kendall Square
Cambridge 42, Mass. TR 6-5230

VIRGINIA
HOLMES, J. NORWOOD
Goldsboro, N. C. RE 4-5008

STOTT, CHAS. G., AND CO., INC.
1310 New York Avenue, N.W.
Washington 5, D.C. NA 8-4181

WASHINGTON
GILL, J. K., CO.
2006 Third Avenue
Seattle 1 MA 4-7111

WEST VIRGINIA
PREISER & COMPANY, B.
416 W. Washington Street
P.O. Box 6118
Charleston 2 DI 3-5515

WISCONSIN
BROSK OFFICE SUPPLY COMPANY
5810 Seventh Avenue
Kenosha OL 4-2193

TRIANGLE SPORT SHOP
314 Bridge Street
Chippewa Falls PA 3-3785

WYOMING
HORBLIT AND COMPANY
2329 Champa Street
Denver 5, Colo. AM 6-2691

LARICK SPECIALTIES, INC.
955 Folsom Avenue
Salt Lake City 4, Utah DA 8-8534

WAYNE IRON WORKS, WAYNE, PENNSYLVANIA

Rolling Gymstands • Folding Bleachers • Outdoor Seating • Folding Partitions • Basketball Backstops • Folding Stages

40M9512—839—8

Digitized by:

ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org

BUILDING
TECHNOLOGY
HERITAGE
LIBRARY

https://archive.org/details/buildingtechnologyheritagelibrary

From the collection of:

Carol J. Dyson, AIA